


Test Profile

Test Parameter	Value
Networks surveyed	ATT - GSM Nextel - iDEN Cingular - GSM Cricket - CDMA Sprint - CDMA Alltel - CDMA Verizon - CDMA
Hardware used	Agilent VoicePrint DTI PN Scanner
Handsets used	ATT - Sagem OT-55-P EFR Nextel - Motorola r370xl Cingular - Sagem OT-55-P EFR Cricket - Kyocera 2235 Sprint - Kyocera 2035 Alltel - Kyocera 2035 Verizon - Kyocera 2135
Software used	Agilent OPAS32 2.71.3 Agilent Nitro 2.1 Microsoft MapPoint Microsoft Excel Microsoft Word
Miles surveyed	Approximately 1200
Data collection window	7:00 a.m. - 7:00 p.m. M-F
Call type	Mobile originated
Call duration	90 seconds
Idle time between calls	30 seconds
Location of Voice Quality Server	EnVision office in Melbourne, FL
Drive test vehicle	Standard mini-van
Handset separation	Minimum of 18 inches
Handset location	Cradles near headrests
Antenna location	External - PN Scanner and GPS Internal - All other handsets
Dates of survey	May 17-28, 2004

Parameters Measured

Parameter	CDMA	iDEN	GSM	IS-136
Forward Link Voice Quality	•	•	•	•
Reverse Link Voice Quality	•	•	•	•
Blocked Calls	•	•	•	•
Dropped Calls	•	•	•	•
No-Service Calls	•	•	•	•
Completed Calls	•	•	•	•
Call Setup Time	•	•	•	•
Mobile RX Power	•	•	•	•
Mobile TX Power	•	•	•	•
RX Qual			•	
FER	•		•	
SOE		•		
BER				•
Aggregate Ec/Io	•			
Strongest Ec/Io				
Analog Mode Calls	•		•	•

Drive Route



Report Contents

- ▶ Executive summary
- ▶ Test methodology description
- ▶ Statistical graphs
- ▶ Geographic plots
- ▶ Raw data in ASCII format
- ▶ Sample available at www.envision-wireless.com